

**Three-phase Line Reactor**

<b>Design</b>	Three-phase, iron-core with air gaps, PolyGap(R) core design
<b>Impregnation</b>	Complete unit vacuum-overpressure impregnated with varnish acc. to temperature class H and temperature hardened in furnace

**Technical Data**

<b>No. of phases</b>		3
<b>Rated voltage</b>	Un/V	600
<b>Rated frequency</b>	fn/Hz	50 / 60
<b>Max operation voltage</b>	Umax/V	690
<b>Impedance</b>		5 % @ 600V, 60Hz
<b>Rated inductivity</b>	Ln/mH	3 x 0.25
<b>RMS current</b>	Irms/A	192
<b>Total losses</b>	Nvsum/W	400
<b>Mass /kg</b>	m/kg	44

**Operating conditions**

<b>Protection class</b>	IP00, Indoor operation	
<b>Type of cooling</b>	AN	natural convection
<b>Isolation class</b>	T50/H	
<b>Minimum ambient temperature</b>	Tamin/°C	5 no condensing, no ice
<b>Maximum ambient temperature</b>	Tamax/°C	50


**Standards**

<b>IEC standards</b>	IEC/EN60076-6 VDE0532-76-6	
<b>UL approval</b>	UL file E173113 class H	
<b>Seperate source voltage</b>	UAC/kV (1 min)	3

**Mechanical characteristics**

<b>Winding material Cu/Al</b>	Al
<b>Terminal 1</b>	Cu bar 30 x 4 mm <sup>2</sup> / 11mm
<b>Terminal 2</b>	Cu bar 30 x 4 mm <sup>2</sup> / 11mm
<b>Ground connect.</b>	safety class I

**Warnungen**

 Nichtbeachtung dieser Hinweise kann zu schweren Verletzungen bis hin zum Tode sowie zur Zerstörung dieses oder angeschlossener Produkte führen!

Im Betrieb können die Produkte hohe Spannungen aufweisen. Berühren Sie die Produkte nicht und schützen Sie die Produkte gegen Berührung. Stellen Sie vor Installations- oder Wartungsarbeiten sicher, dass die Produkte spannungsfrei geschaltet sind und keine Restspannungen mehr aufweisen. Betreiben Sie keine Produkte, die beschädigt sind. Die Installation darf nur von fachlich geschultem Personal durchgeführt werden. Die angegebenen technischen Daten sind typisch. Aufgrund von Material- und Fertigungseigenschaften können Abweichungen auftreten. Änderungen vorbehalten.

**Cautions**

 Noncompliance with these instructions may lead to serious injury, death, or damage to the products and connected equipment.


All electrically active parts may carry high voltages. Do not touch the products during operation and protect the products against accidental contact. Before any assembly or maintenance make sure that all equipment is disconnected from the power source and is free of residual voltage.


Do not install products in case of any visible damage. Installation must be done by skilled personnel only.

All given technical specification are typical. Material and production tolerances may cause variations. This datasheet may be subject to change.

**Name Plate**

zeichnungen/tschild/pdf/AK1069408.JPG

<b>MANGOLDT</b> 		Hans von Mangoldt GmbH 52080 Aachen, Germany	
<b>LINE REACTOR - ACL65-0192</b>			
TYP	1069408	Nr {999999999}	IEC60076
LN/mH	0,25	UN/V 600	IP00
I <sub>rms</sub> /A	192	fN/Hz 50/60	{9999}
uk/%	5	ED/% 100	44,0 kg AN-T50/H
Made in Germany			



AK-Nr. (Code-No.):	ACL65-0192	Gewicht:	44 kg
Projektionmethode	ISO 5456:2	Kunde	LINE REACTOR 3U1150/75L
Blatt	1	Catalog No.	554032
Blatt Anz.	1	LN [mH]	0.26
Projektionssymbol		UN [V]	600
Allg. Toleranzen nach	ISO 2768-v	Irms [A]	192
gezeichnet	16.03.2018	Name	M. Esser
geprüft		Name	Hans von Mangoldt GmbH
Datum		Adresse	Hergelsbendenstraße 18 D-52080 Aachen
Index		Datum	
Änderungstext		Name	
Maßstab	1:4	Datum	
Format	A3	Name	