

Three-phase Sine Wave Filter Reactor

Design	Three-phase, iron-core with air gaps, PolyGap(R) core design
---------------	--

Impregnation	Complete unit vacuum-overpressure impregnated with varnish acc. to temperature class H and temperature hardened in furnace
---------------------	--

Technical Data

No. of phases		3
Rated voltage	Un/V	500
Rated frequency	fn/Hz	80
Rated inductivity	Ln/mH	3 x 0.06
Negative tolerance	%	-5
Positive tolerance	%	+5
Rated capacity (Y)	µF	-
Rated capacity (D)	µF	-
Voltage Drop	Vph	23.0
RMS current	Irms/A	1,220
Losses of fundamental	Nv1/W	311
Total losses	Nvsum/W	3,400
Mass /kg	m/kg	468

Operating conditions


Protection class	IP00, Indoor operation		
Operation mode	Continuous mode		
Duty cycle	%	100	
Min. switching frequency	kHz	2	
Max. switching frequency	kHz	10	
Maximum elevation	masl	1,000	
Type of cooling	AN	natural convection	
Isolation class	T45/H		
Minimum ambient temperature	Tamin/°C	-25	no condensing, no ice
Maximum ambient temperature	Tamax/°C	45	
Allowed temperature rise	dT/K	120	utilized acc. to isolation class H
Temperature sensor	No		
Temperature sensor middle coil	prepared		

Connection Drawing



Standards	
IEC standards	IEC/EN60076-6 VDE0532-76-6
UL approval	UL file E173113 class H
Seperate source voltage	UAC/kV (1 min) 3
Mechanical characteristics	
Mounting	base mounting only
Winding material Cu/Al	Al
Terminal 1	Cu bar 80 x 8 mm ² / 14mm / 25-30Nm
Terminal 2	Cu bar 80 x 8 mm ² / 14mm / 25-30Nm
Ground connect.	safety class I
Bandage	Klebeband G 565 UL ID 1042646

zeichnungen/pre/Datei-nicht-gefunden.bmp



Warnungen



Nichtbeachtung dieser Hinweise kann zu schweren Verletzungen bis hin zum Tode sowie zur Zerstörung dieses oder angeschlossener Produkte führen!

Im Betrieb können die Produkte hohe Spannungen aufweisen. Berühren Sie die Produkte nicht und schützen Sie die Produkte gegen Berührung.

Stellen Sie vor Installations- oder Wartungsarbeiten sicher, dass die Produkte spannungsfrei geschaltet sind und keine Restspannungen mehr aufweisen.

Betreiben Sie keine Produkte, die beschädigt sind. Die Installation darf nur von fachlich geschultem Personal durchgeführt werden.

Die angegebenen technischen Daten sind typisch. Aufgrund von Material- und Fertigungseigenschaften können Abweichungen auftreten.

Änderungen vorbehalten.

Cautions



Noncompliance with these instructions may lead to serious injury, death, or damage to the products and connected equipment.

All electrically active parts may carry high voltages. Do not touch the products during operation and protect the products against accidental contact.


Before any assembly or maintenance make sure that all equipment is disconnected from the power source and is free of residual voltage.

Do not install products in case of any visible damage. Installation must be done by skilled personnel only.

All given technical specification are typical. Material and production tolerances may cause variations. This datasheet may be subject to change.

Name Plate

zeichnungen/tschild/pdf/AK1062933.JPG

MANGOLDT 		Hans von Mangoldt GmbH 52080 Aachen, Germany	
SINE FILTER REACTOR - PSD53-1220-00			
TYP	1062933	Nr {999999999}	IEC60076
LN/μH	60	UN/V	500 IP00
IN/A	1220	fN/Hz	80 {9999}
fSW/kHz	2-10	ED/%	100 468 kg
			AN-T45/H
Made in Germany			